



PERPENDICULAR RUN

PARALLEL RUN

12-14 x 1-1/2" SELF-DRILLING FASTENER

12-14 x 2" SELF-DRILLING FASTENER

4" WIDE HIT SECTION FOR PERPENDICULAR RUN

4" WIDE SUPPORT PLATE FOR PARALLEL RUN

INSTALLATION NOTES

- SUPPORT PLATES SHOULD BE LOCKED OVER PURLINS AND SPACED TO MORE THAN 30" ON CENTER
- PROVIDE 1" WIDE x 3/16" MASTIC (NOT SUPPLIED) OVER INS PRIOR TO SETTING SUPPORT PLATES
- GRATING SHOULD BE BUTTED END TO END OVER SUPPORTS
- CONSULT ROOF MANUFACTURER FOR SPECIFIC INSTRUCTIONS AND WARRANTY INFORMATION

CONTRACTOR:
JOB/LOCATION:
DATE:
WIDTH: 36"
ROOF WALK GAUGE: 18 GA.
LENGTH PARALLEL:
LENGTH PERPENDICULAR:

MAXIMUM SUPPORT PLATE SPACING 30" OVER PURLINS

METAL ROOF WALKWAYS

RW36-HR-PC-SR

PERPENDICULAR SECTION PITCH CORRECTED

PARALLEL SECTION PLANKS & RAILS NOT PITCH CORRECTED

HANDRAILS ONE SIDE ONLY

R & S SALES COMPANY, INC.
3575 OLD CONEJO ROAD
NEWBURY PARK, CA 91320
PHONE 805-375-3980
FAX 805-375-3981