


-  M CLIP
- 12-14 x 1-1/4" SELF-DRILLING FASTENER
- 12-14 x 3" SELF-DRILLING FASTENER
- 48" WIDE HAT SECTION FOR PERPENDICULAR RUN
- 48" WIDE LEDGER
- 48" SUPPORT PLATE FOR PARALLEL RUN

INSTALLATION NOTES:

1. OPTION, THE PERPENDICULAR RUN CAN CROSS THE PARALLEL RUN IF NEEDED.
2. SUPPORT PLATES SHOULD BE LOCATED OVER PURLINS AND SPACED NO MORE THAN 5'0" ON CENTER.
3. PROVIDE 1" WIDE x 3/16" MASTIC (NOT SUPPLIED) OVER RIBS PRIOR TO SETTING SUPPORT PLATES.
4. GRATING SHOULD BE BUTTED END TO END OVER SUPPORTS.
5. CONSULT ROOF MANUFACTURER FOR SPECIFIC INSTRUCTIONS AND WARRANTY INFORMATION.

CONTRACTOR:
JOB/LOCATION:
WIDTH: 36"
ROOF WALK GAUGE: 18 GAUGE
LENGTH PARALLEL:
LENGTH PERPENDICULAR:

METAL ROOF WALKWAYS RW36-HR
R & S MANUFACTURING AND SALES COMPANY, INC.
 3575 OLD CONEJO ROAD
 NEWBURY PARK, CA 91320
 PHONE: 805-375-3980
 FAX: 805-375-3981