



- M8 FLAT WASHER
- ⊥ M8-50 HEX HEAD CAP BOLT
- ⊥ 12-14 x 1-1/4" SELF-DRILLING FASTENER
- ⊥ 12-14 x 3" SELF-DRILLING FASTENER
- ⊥ "M" WASHER
- ⊥ S-5 BLOCK
- 48" WIDE LEDGER ANGLE
- 48" WIDE SUPPORT PLATE FOR PERPENDICULAR RUN
- 48" WIDE SUPPORT PLATE FOR PARALLEL RUN

INSTALLATION NOTES

- * SUPPORT PLATES ARE LOCATED OVER PURLINS - SPACE NO MORE THAN 5'0" ON CENTER
- * INSTALL S-5 BLOCKS OVER SEAMS AND TIGHTEN M8 BOLTS
- * GRATING SHOULD BE BUTTED END TO END OVER SUPPORTS
- * ATTACH PLANKS ON SUPPORT PLATES USING 3" SELF DRILLING FASTENERS AND "M" WASHERS
- * GRATING AND SAFETY RAILS RUN PARALLEL TO ROOF PANELS (NOT PITCH CORRECTED)
- * CONSULT ROOF MANUFACTURER FOR SPECIFIC INSTRUCTIONS AND WARRANTY INFORMATION
- * ROOFWALK PLANKS, SUPPORTS, AND HANDRAILS WEIGH APPROXIMATELY 20 LBS/FT

CONTRACTOR:
 JOB/LOCATION:
 DATE:
 WIDTH: 36"
 ROOF WALK GAUGE: 18 gauge
 LENGTH PARALLEL:
 LENGTH PERPENDICULAR:

METAL ROOF WALKWAYS

RW36-SS SAFETY RAIL ONE SIDE NON-PITCHED	R & S MANUFACTURING AND SALES COMPANY, INC. 3575 OLD CONEJO ROAD NEWBURY PARK, CA 91320 PHONE 805-375-3980 FAX 805-375-3981
---	--