


- M8 FLAT WASHER
- ⌋ M8-50 HEX HEAD CAP BOLT
- ⌋ 12-14 x 1-1/4" SELF-DRILLING FASTENER
- ⌋ 12-14 x 3" SELF-DRILLING FASTENER
- ⌋ "M" WASHER
- ⊠ S-5 BLOCK



INSTALLATION NOTES

- * SUPPORT PLATES ARE LOCATED OVER PURLINS - SPACE NO MORE THAN 5'0" ON CENTER
- * ATTACH PLANKS ON SUPPORT PLATES USING 3" SELF-DRILLING SCREWS AND "M" WASHER
- * GRATING SHOULD BE BUTTED END TO END OVER SUPPORTS AND SPLICE PLATES
- * PARALLEL RUNS MUST RUN THROUGH THE PERPENDICULAR RUNS
- * INSTALL S-5 BLOCKS OVER SEAMS AND TIGHTEN M8 BOLTS
- * CONSULT ROOF MANUFACTURER FOR SPECIFIC INSTRUCTIONS AND WARRANTY INFORMATION
- * ROOFWALK PLANKS AND SUPPORTS WEIGH APPROXIMATELY 10 LBS/FT

CONTRACTOR
 JOB/LOCATION
 DATE
 WIDTH: 36"
 ROOF WALK GAUGE: 18 GA
 LENGTH PARALLEL
 LENGTH PERPENDICULAR

METAL ROOF WALKWAYS

RW36-55

R # 5 MANUFACTURING AND SALES COMPANY, INC.
 3575 OLD CONEJO ROAD
 NEWBURY PARK, CA 91320
 PHONE 805-375-3980
 FAX 805-375-3981