



- ⊙ 5/16" FLAT WASHER
- ⌋ 1/4" x (SEE BELOW)" HEX HEAD CAP BOLT
* ULTRADEK, STARSHIELD, SSII, & VPSSR = 3-1/2"
* BUTLER MR24 = 3"
- ⌋ 1/4" x (SEE BELOW)" HEX HEAD CAP BOLT
* ULTRADEK, STARSHIELD, SSII, & VPSSR = 1-1/2"
* BUTLER MR24 = 1"
- ⌋ 12-14 x 1-1/4" SELF-DRILLING FASTENER
- ⌋ 12-14 x 3" SELF-DRILLING FASTENER
- ⌋ "M" WASHER
- ⌋ 1/4"-20 J TYPE RETAINER
- ⌋ 30" WIDE LEDGER ANGLE
- ⌋ SPLICE PLATE
- ⌋ 30" WIDE SUPPORT PLATE FOR PARALLEL RUN

INSTALLATION NOTES

- * SUPPORT PLATES SHOULD BE LOCATED OVER PURLINS AND SPACED NO MORE THAN 5'0" ON CENTER
- * ATTACH PLANKS ON SUPPORT PLATES USING 3" SELF-DRILLING SCREWS AND "M" WASHER
- * GRATING SHOULD BE BUTTED END TO END OVER SUPPORTS AND SPLICE PLATES
- * INSTALL RIB CLIPS UNDER SEAMS AND TIGHTEN 1/4" BOLTS
- * CONSULT ROOF MANUFACTURER FOR SPECIFIC INSTRUCTIONS AND WARRANTY INFORMATION
- * ROOFWALK PLANKS AND SUPPORTS WEIGH APPROXIMATELY 9 LBS/FT.

CONTRACTOR _____

JOB/LOCATION _____

DATE _____

WIDTH _____

ROOF WALK GAUGE _____

LENGTH PARALLEL _____

LENGTH PERPENDICULAR _____

MAXIMUM SUPPORT PLATE SPACING 5'0". LOCATE OVER PURLINS

METAL ROOF WALKWAYS RW24-SS

R & S SALES COMPANY, INC.
 3575 OLD CONEJO ROAD
 NEWBURY PARK, CA 91320
 PHONE 805-375-3980
 FAX 805-375-3981